

CHAMBERS COUNTY HIGHWAY DEPARTMENT

Josh Harvill
County Engineer

Daniel Lundy
Assistant County Engineer

PO Box 650
Lafayette, AL 36862
Telephone: 334-864-4377
Fax: 334-864-7850



COMMISSIONERS

CHARLIE WILLIAMS, DIST. 1
JAMES BROWN, DIST. 2
JOE BLANKS, DIST. 3
HENRY OSBORNE, DIST. 4
DAVID EASTRIDGE, DIST. 5
DEBBIE WOOD, DIST. 6

Date _____

Dear Sir:

Enclosed you will find a bid for Cold Plant Mix. If you are interested in bidding, please complete the form and return it to:

Chambers County Highway Department
INQUIRY # _____
P. O. Box 650
LaFayette, Alabama 36862

Notice that all bids must be received no later than 10:00 a.m. Central Time
_____. All bids should be in individual envelopes with the
APPROPRIATE INQUIRY NUMBER shown on the outside of the envelope.

If you have any questions, please call the County Engineer's Office at 334-864-4377.

Sincerely,

A handwritten signature in blue ink, appearing to read "Josh Harvill".

Josh Harvill
County Engineer

Enclosure

**STATE OF ALABAMA
CHAMBERS COUNTY
CHAMBERS COUNTY COMMISSION
LAFAYETTE, ALABAMA**

Gentlemen:

Sealed bids will be received by the Purchasing Agent at the Highway Department in LaFayette, Alabama until the above time and date, and then opened as soon thereafter as practicable for furnishing the items listed below, f. o. b. points shown: If you are unable to furnish an item as specified and desires to offer a substitute please give full description of the items offered as substitutes, otherwise your quotations will not be considered. If no exception is made on bid sheet, it will be assumed that the bidder is offering the articles specified. Bidders must indicate the brand or make of items they propose to furnish.

Purchasing Agent

COLD PLANT MIX BITUMINOUS PATCHING MATERIAL

The material specified in this inquiry shall consist of cold plant mixed patching material composed of a mixture of aggregates and bituminous material prepared in accordance with the following specifications:

AGGREGATES: Aggregates shall conform to section 416.02, mix "A", materials shall conform to the current Alabama Department of Transportation Standard Specifications.

The aggregates shall be heated to a temperature sufficient to dry the aggregate and then cooled to 200 degrees Fahrenheit before applying the bituminous material.

ASPHALT CEMENT & LIQUEFIER: Asphalt, cement, Grade AC-20 shall be used in mixing the patching material.

Asphalt cement content of mix will be a 4.0 to 7.0 percent, by weight. The Chambers County Highway Department Engineering office will specify the exact asphalt cement content.

Liquefier shall be slowly volatile petroleum oil, free from water, conforming to the following specifications:

Initial boiling point	Min. 200 degrees F
End Point	Max. 635 degrees F
Recovery, percent	Minimum 94

The Chambers County Highway Department Engineering Office will specify the exact liquefier content.

Asphalt cement and liquefier shall have a combined temperature of 200 degrees Fahrenheit to 225 degrees Fahrenheit when introduced into the mixer.

Inquiry No. _____

To be received, no later than:
10:00 a.m. CST.

PREPARATION OF MIXTURE:

The aggregates shall be introduced into the mixer prior to the addition of the asphalt cement. The asphalt cement shall be introduced and mixing continued until the aggregates are thoroughly coated. The liquefier in the specified amount shall then be added to the mix. Mixing shall continue during the addition of the liquefier and until thorough coating of the aggregates is obtained.

If approved by the Engineer, liquefier may be added to the asphalt cement by an in-line bleeding process, which permits uniform distribution of the liquefier at the percentage rate, specified. The liquefier and asphalt combination shall be introduced into the mixer with mixing continuing until all aggregate particles are thoroughly coated.

METHOD OF MEASUREMENT:

The quantities to be paid for under this inquiry shall be the weight in tons of cold plant mixed patching material for maintenance purposes picked up at vendor’s plant or delivered to the Chambers County Highway Department Shop in LaFayette, Alabama. The weight of the mixture shall be determined from batch weights, certified railroad car weights, truck scale weights, or other methods approved by the Engineer. The producer shall furnish all scales and other equipment, meeting the approval of the engineer, as may be necessary for the proper determination of the weights.

Materials picked up at Vendor’s Plant: \$ _____ per ton.

Materials delivered to LaFayette, AL Shop: \$ _____ per ton.

If mutually agreeable, after the original bid year, this contract can be renewed at a maximum of two one-year periods.

ALL BIDDERS MUST USE OUR BID FORM AND MUST SHOW ON FACE OF ENVELOPE CONTAINING BID, THE INQUIRY NUMBER AND OPENING DATE. FAILURE TO COMPLY WITH THIS MAY RESULT IN YOUR BID NOT BEING CONSIDERED.

HOURS OF OPERATION ARE AS FOLLOWS

Monday-Thursday

6:00 a.m. to 4:30 p.m.

Please call for alternate address if bid is to be delivered outside of our normal operating hours.

Please remit all Bids and Inquiries to the following address.

The Inquiry Number must be included in the remittance address

CHAMBERS COUNTY ENGINEER

INQUIRY # _____

P.O. BOX 650

LAFAYETTE, AL 36862

**WARNING !!! No errors will be corrected after Bids are opened. No price
Shall include State or Federal Excise Taxes. Tax exemption certificates furnished upon request.**

Inquiry No. _____

To be received, no later than:
10:00 a.m. CST.

We are in position to furnish the above at the prices shown and can make shipment within _____ days after receipt of order.

I hereby affirm I have not been in any agreement or collusion among bidders or prospective bidders in restraint of freedom of competition, by agreement to bid at a fixed priced or to refrain from bidding or otherwise.

THIS BID MUST BE NOTARIZED.

Sworn to and subscribed before me

This the _____ day of _____, 20_____.

Notary Public

Firm: _____

By: _____

Street Address: _____

City: _____

Terms: _____

Date: _____

Email: _____

Telephone: _____

IMPORTANT: Any attachment hereto is made and becomes a part of this inquiry and must be signed by Bidder.